

VT-BC504A

Explosion Proof Camera Housing with Cooling Function

IP68



- window size $\Phi 75\text{mm}$
- Inside size $\Phi 100 \times 300\text{mm}$
- ATEX Zone 1&2 / 21&22
- 200-degree high temperature Housing
- Double-layer structure, water & wind cold
- Made of 304 stainless steel material (316,316L for optional)

EX Marking



Certification



Markets



 Specification	Ex-Level	ATEX
	Ingress Protection level	IP68
	Max Temperature of Windows	≤150°C
	Relative humidity	≤ 95% (+25°C)
	pressured air temperature	≤30°C
	Air pressure	0.1~0.3Mpa
	Air flow rate	0.1~0.3m3/min
	Atmospheric pressure	80kpa~106 kpa
	Thermostat System	optional
	Supply voltage	DC12V /AC220V (optional)
	Suitable Environment	Apply to explosive gas and combustile dust environment
	Material	304 stainless steel
	inlet interface specifications	G1/4 for air cooling, G1/2" x 2 for output cable
	External dimensions	350x140x160mm
	inside dimension	Φ100mm*300mm (length)
	Windows area	Φ60
	Installation method	PTZ, Wall Hanging dyadic, fixed bracket, Pillar base



WV-U1132A
WV-U1142A



[WV-U1132A Product Data Sheet](#)
[WV-U1142A Product Data Sheet](#)



WV-S1132
WV-S1136A



[WV-S1132 Product Data Sheet](#)
[WV-S1136A Product Data Sheet](#)



NBN-73023-BA



[NBN-73023-BA Product Data Sheet](#)

VT-B02 Bracket for B series



VT-B04 Bracket for B series



VT-B03 Bracket for B series

