VT-BW503

V-TECH Explosion Proof Bullet Housing

IP68

- window size: Φ60mm
- ATEX Zone 1&2 / 21&22
- Inside size: Φ100*290mm
- Made of 304 stainless steel material (316,316L for optional)
- Usual power sull: AC220V/DC12V, other Power mode can be customized
- Class I Division 1&2 / Class II Division 1&2 and all the rest except zone 0
- Fixed focus or zoom camera can be loaded

EX Marking

EXD EXTB T6

Certification

Markets

Specification
VT-BW503

	Ex-Level	ATEX II 2G Ex d IIC T6 Gb II 2D Ex tb IIIC IP68 T80℃ Db
	Ingress Protection level	IP68
specifications	Temperature range	-40℃～60℃
	Relative humidity	≤ 95%（+25°C)
	Atmospheric pressure	80kpa～106 kpa
	Thermostat System	Optional
	Supply voltage	DC12V /AC220V（optional）
	Material	304 stainless steel (316, 316L for optional)
	Inlet interface specifications	2pcs M25*1.5 output (original G3/4)
	Inside dimension	Φ100mm*290mm（length ）
	Windows area	Φ60
	Applicable environment	Apply to explosive gas and combustible dust environment
	Installation method	PTZ, Wall Hanging dyadic, fixed bracket, Pillar base

WV-U1132A
WV-U1142A

WV-U1132A Product Data Sheet
WV-U1142A Product Data Sheet

WV-S1132
WV-S1136A

WV-S1132 Product Data Sheet
WV-S1136A Product Data Sheet

NBN-73023-BA

NBN-73023-BA Product Data Sheet

VT-B02
Bracket for B series

VT-B04
Bracket for B series

VT-B03
Bracket for B series